



Front View



View: Front Face 9pin socket
Connects to Mixer (M)


Rear View




View: Rear 9pin socket (solder cups)
Connects to Mixer (M)



Straight Through
Vacuum grade solder
Qty: 4
Length: various



View: Front Face 9pin male
Connects to 12K Bulkhead (S)



View: Rear 9pin male (solder cups)
Connects to 12K Bulkhead (S)

9 Pin ITT Cannon Connector

File: Coldstage-SISbias_Pigtail.dwg

J.W. Kooi/06-Feb-2010

DESCRIPTION: SIS Bias connector 'Pig-tail', 12K to 4K mixer block	Sidecab Dewar(s)	9 Pin, Female, Chassis Mount
A (1) - A (1), 1 Vbias		
B (2) - B(2) +Isense		
C (3) - C(3) +Vsense / - Isense		
D (4) - D(4) -Vsense		
E (5) - E(5) GND		
F (6) - F(6) GND		
G (7) - 1 NC		
H (8) - 1 NC		
J (9) : 1 NC		

Cable length 230/345 R: 3.0 inches (3mil Manganin)

230/345 L: 4 /5/8 inches (3 mil Manganin or 5 mil Manganin)

460/650 L: 6.0 inches (3 mil Manganin or 5 mil Manganin)

460/650 R: 7 3/8 inches (3 mil Manganin or 5 mil Manganin):