

L.O. Materials 12-5-2012

Qty	Value	Type	Body	Ref. Designator
2	1 μ f		1210	C1, 9
3	100pf		805	C15 - 17
11	0.1 μ f		805	C2 - 6, 8, 10 - 14
1	.33 μ f		805	C7
2		TSMAD16A	1206	D1, 2
6		6 PIN HEADER	SIP	J1, 2, 5 - 8
1		20 PIN HEADER	SIP	J10
1		8 PIN HEADER	SIP	J3
1		SMA CONN.	SMA	J4
1		16 PIN HEADER	SIP	J9
1		V23026	RELAY	K1
5		BLM 31	1206	L1 - 5
6	2.7k		805	R1, 36 - 40
2	3.3k		805	R10, 11
9	1k		805	R12, 13, 29, 41, 49, 61, 72 - 74
1	43k		805	R16
16	10k		805	R2, 8, 14, 15, 17 - 19, 27, 30, 50 - 52, 57, 67, 68, 78
2	8.2k		805	R20, 24
2	2k	POT		R21, 25
2	3.9k		805	R22, 26
2	100k		805	R23, 75

L.O. Materials 12-5-2012

Qty	Value	Type	Body	Ref. Designator
6	200Ω		805	R3, 31 - 35
15	2.2k		805	R4, 5, 42 - 48, 58 - 60, 62 - 64
4	.5Ω	1/2 WATT	2010	R6, 69 - 71
1	TBD	R_DUMMY	805	R65 DNI
2	10k	POT		R7, 76
1	100k	POT		R77
8	20k		805	R9, 28, 53 - 56, 66, 79
1		DRDNB21D	SOT 363	U1
1		ADUM1410	SOIC 16	U11
1		UA78M05CDCY	SOT 223	U2
1		UA79M05CKVU- RG3	TO 252	U3
4		OPA2348 REPL. W/ OPA2234	SOIC 8	U4, 5, 9, 10
2		TLC3702	SOIC 8	U6, 7
1		SN74LVC1G08	SOT	U8